Mud Sucker® **Diaphragm Pumps**

B Series

Solids Handling Diaphragm Pumps

: 4B-M™ Standard Piping **Engine Driven**





Performance Range

Max. capacity	110 GPM		
Max. suction lift	25'vertical or 75' horizontal		
Max. discharge head	50' vertical or 300' horizontal		
Solids handling	2¼" dia or 50% by volume		

Pump and Motor Specifications

Suction inlet/outlet size	4"x4"			
Max. liquid temperature	104°F (40°C) continuous			
Pump body casing	Cast iron (ASTM A356, Class 30)			
Diaphragm	14¾" dia thermoplastic elastomer (red) Severe duty -25°F to 212°F Optional: Neoprene			
Ball valves	5-1/8" diameter polyurethane with steel core			
Gearbox	Helical bevel cast iron housing with heat treated gears			
Hardware	Zinc plated			
Rod end bearing body	Cast iron, protective coated for corrosion resistance			
Ball bearing	Cast iron , protective coating for corrosio resistance			
Ultimate radial static load capacity	9,000 Lbs			

Motor Options

Description	Part No.	Motor Option	Motor Option	
Gas Engine	61727-00	9 hp, Honda GX270		
Diesel Engine	61727-10	6.5 hp, Kohler/Yanmar		


FEATURES

4" Connection size Pump up to 110 GPM Transfer spherical solids up to 2¼" or 50% by volume Pump up to 50' vertical or 300' horizontal

14¾" heavy duty diaphragm

Multiple drive options and industry specific components

PROFESSION



Professional Options for Professional Applications





.....

4B Series - Dolly Mounted



4B Series - In-line Configuration

Mud Sucker[®] Diaphragm Pumps

Toll-Free North America 1.888.829.2783

Worldwide 201.445.2882

Website http://www.wastecorp.com

E-mail info@wastecorp.com



Mud Sucker B Series pumps are designed and specified to pump landfill leachate, agricultural waste, select manure pumping applications, mining waste, bauxite waste pumping, waste oil, biodiesel applications, coal slurry, tar sands applications, aquaculture, industrial fluids and more. Consult factory with flow rates and percentage of solids you are pumping before ordering. © Wastecorp, no reproduction without authorization



	Part no.	Description		Part no.	Description
	19022-00	Recommended! Pressure relief valve, bronze set at 40 psi	*	61747-00	Utility trailer (non-DOT) w/2" ball hitch
	61740-00	Basic spare parts kit (diaphragm and flappers)		61741-00	Comprehensive spare parts kit (diaphragm, flap- pers gaskets, weights and hardware)
	60728-00	Non-collapsible EPDM hose 2"x20'. Camlocks included		Various	Wet section coatings for specific applications
	51333-10	Discharge hose, lay flat (brown) 2"x50'. Camlocks included		60469-00	Camlock fitting 4" alum. male adapter MNPT
NATE OF STREET	34383-00	Stainer, sq. hole (solids) 2" FNPT	5	60506-00	The Gulper™ Suction tool No more bending
Mark	61387-00	Universal sewer adapter assem- bly	TE	61537-00	Clear swing check valve 4" FPTxFPT