



# Compact Dual Compartment Vacuum Trailers Helps You Get More Done.

#### **FEATURES**

- Fresh water or raw water compartments available
- Premium galvanized trailer system with diamond plate deck
- Several vacuum pump options available
- Low profile design to work in areas with height restrictions
- Heavy duty steel tank with sight eyes and manway options
- Rugged construction with heavy duty frames and axles so your machine will outlast
- Fast tank emptying with reverse flow available
- Premium hoses available in a variety of lengths

### THE SUPER DUTY IS MADE FOR

- Septic waste pumping
- Portable toilet servicing
- General wastewater cleanup
- Clean out car wash sediment pits
- Storm drain, catch basin pumping and cleaning
- Septic tank pumping



## **TVP-200-100 SPECIFICATIONS**

Vacuum/Pressure   127CFM   230 CFM   350 CF	Model	TVP-200-100-DT(127)	TVP-200-100-DT(230)	TVP-300-DT(350)			
Part Number	Vacuum/Pressure	127CFM	230 CFM	350 CFM	-		
Tank         200 US gallons waste. 100 US gallons water.           Base Frame         Heavy Duty Fabricated Steel           Tank Material         A36 Carbon Steel           Sight Eyes         12° Rear Mount Swing Door           Hose Rack         12° Rear Mount Swing Door           Hose Rack         14° Hp Honda/Kohler Sore is de of tank           Foliane           By he Honda/Kohler Gas         14 hp Honda/Kohler Sas Sas Satart         24 hp Kohler/Deutz         12° Rear Mount Sas E-Start         24 hp Kohler/Deutz         12° Rear Mount Sas E-Start         24 hp Kohler/Deutz         12° Rear Mount Sas E-Start	Typical applications		Septic Tank / Sump Pits /	Heavy Drilling fluids			
Capacity         300 US gallons waster, 100 US gallons water           Base Frame         Heavy Duty Fabricated Steel           Tank Material         A36 Carbon Steel           Sight Eyes         (2) 5° Glass           Manway         12" Rear Mount Swing Door           Hose Rack         5° Honda/Kohler Gas           Forgine         9 hp Honda/Kohler Gas         14 hp Honda/Kohler Gas         24 hp Honda/Kohler Data         Case Estart           Optional Engine         10 hp Hatz Diesel         17 hp Hatz Diesel         24 hp Kohler/Deutz         Cestart           Fower Transmission           Trailier Specs         Galvanized single 5200# Axle, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck           Hitch         Select: 2° Ball, 2 5′16° ball, 3° Pintle           Wheels         Safety Case           Trailer Specs         Galvanized spoke           Tires         ST225/75R15           Jackstand         To Tapproved 7 way connector           Lighting System         DOT approved 7 way connector           Lighting System         DOT approved 2 with with with with with with with with	Part Number	64955-10	64955-15	64955-45			
Base Frame         Heavy Duty Fabricated Steel           Tank Material         A36 Carbon Steel           Sight Eyes         (2) 5" Glass           Manway         12" Rear Mount Swing Door           Hose Rack         12" Rear Mount Swing Door           Begine         9 hp Honda/Kohler Gas E-Start         24 hp Honda/Kohler Gas E-Start           Gas Engine         10 hp Hatz Diesel E-Start         17 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start           Power Transmission         Belt Driven           Foster         Belt Driven           Foster         Belt Driven           Foster         Belt Driven           Foster         Belt Driven	Tank						
Tank Material         A 36 Carbon Steel           Sight Eyes         (2) 5" Glass           Manway         12" Rear Mount Swing Door           Hose Rack         12" Rear Mount Swing Door           Bragine         6 bp Honda/Kohler Gas Ergine         24 hp Honda/Kohler Gas Erstart           Gas Engine         8 bp Honda/Kohler Gas Erstart         24 hp Honda/Kohler Gas Erstart         24 hp Kohler/Deutz Gas Erstart         Proper Transines           Optional Engine         10 hp Hatz Diesel Erstart         24 hp Kohler/Deutz Diesel Erstart         Proper Transines         Proper Transines         Belt Driven         Proper Transines         Belt Driven         Proper Transines         Belt Driven         Proper Transines         Belt Driven         Proper Transines         Select: 2" Ball, 2 5/16" ball, 3" Pintle         Select Plate Deck         Proper Transines         Belt Driven         Proper Transines         Belt Driven         Proper Transines         Belt Driven         Proper Transines         Select: 2" Ball, 2 5/16" ball, 3" Pintle         Belt Driven         Proper Transines         Belt Driven         Belt Driven Proper Transines         Belt Driven Proper Transines	Capacity		200 US gallons waste	100 US gallons water			
Sight Eyes         (2) 5° Glass           Manway         12" Rear Mount Swing Door           Hose Rack         (2) Hooks on rear or side of tank           Engine         9 hp Honda/Kohler Gas E-Start         24 hp Honda/Kohler Gas Gas E-Start           Optional Engine         9 hp Honda/Kohler Gas E-Start         14 hp Honda/Kohler Gas Gas E-Start         24 hp Kohler/Deutz Gas E-Start         Cestart           Power Transmission         Belt Driven         Festart           Trailer Specs         Galvanized single 5 20# Axie, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck         Hother Deck Plate Deck           Hitch         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Galvanized single 5 20# Axie, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck           Hitch         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Galvanized spoke           Tiraler and brake supply         DOT approved Zmor.pote by Select: 2" Ball, 2 5/16" ball, 3" Pintle           Safety Chains         DOT approved LED           Safety Chains         DOT approved LED           Safety Chains         DOT approved LED           Suction Hose         30 ft Non-Collapsible with Alu	Base Frame		Heavy Duty Fa	abricated Steel			
Manway         12" Rear Mount Swing Door           Hose Rack         (2) Hooks on rear or side of tank           Engine         Fisher           Gas Engine         9 hp Honda/Kohler Gas E-Start           Optional Engine         10 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start           Power Transmission         Belt Driven           Trailer           Trailer Specs         Galvanized single Substand Sale Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Select: 2" Ball, 3" Pintle           Select: 3" Ball, 2 5/16" ball, 3" Pintle           Wheels           Select: 3" Ball, 2 5/16" ball, 3" Pintle           Select: 4" Ball, 2 5/16" ball, 3" Pintle           Select: 4" Ball, 2 5/16" ball, 3" Pintle           Select: 4" Ball, 2 5/16" ball, 3" Pintle           Ball All All All All All All All All All	Tank Material		A36 Cart	oon Steel			
Fingine         (2) Hooks on restricted of tank           Gas Engine         9 hp Honda/Kohler Gas E-Start         24 hp Honda/Kohler Gas Gas E-Start         24 hp Kohler/Deutz Gas E-Start         25 start         25 start         25 start         26 start         26 start         26 start         26 start         27 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start         26 start         26 start         27 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start         26 start         27 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start         26 start         27 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start         27 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start         27 hp Hatz Diesel E-Start         28 hp Hatz Diesel E-Start         <	Sight Eyes		(2) 5"	Glass			
Engine         9 hp Honda/Kohler Gas E-Start         14 hp Honda/Kohler Gas Gas E-Start         24 hp Honda/Kohler Gas Gas E-Start         24 hp Honda/Kohler Gas Gas E-Start         24 hp Kohler/Deutz Gas E-Start           Optional Engine         10 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start           Power Transmission         Belt Driven         ************************************	Manway		12" Rear Mou	nt Swing Door			
Gas Engine         9 hp Honda/Kohler Gas E-Start         14 hp Honda/Kohler Gas E-Start         24 hp Honda/Kohler Gas E-Start         24 hp Honda/Kohler Gas E-Start           Optional Engine         10 hp Hatz Diesel E-Start         17 hp Hatz Diesel E-Start         24 hp Kohler/Deutz Diesel E-Start           Power Transmission         Trailer Specs         Galvanized single 50# Axle, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck           Hitch         Select: 2° Ball, 2° 516° ball, 3° Pintle           Wheels         Select: 2° Ball, 2° 516° ball, 3° Pintle           Wheels         Select: 2° Ball, 2° 516° ball, 3° Pintle           Wheels         Select: 3° ST1225/75R15           Jackstand         To Tapproved To way connector           Lighting System         DOT approved t ED           Safety Chains         DOT approved t ED           Safety Chains         Suction Hose         30 ft Nor-Callapsible with Alum. Cambox kiltings (longer lengths available)           Discharge Hose         Port Size           Suction Port Size         2" lever valve with Cambock         3° Lever Valve with Cambock         2" Lever Valv	Hose Rack		(2) Hooks on rea	ar or side of tank			
Potentian   Pote	Engine						
Power Transmission   Belt Driven	Gas Engine						
Trailer           Trailer Specs         Galvanized single 5200# Axle, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck           Hitch         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Galvanized spoke           Tires         \$T225/75R15           Jackstand         7,000 lbs           Trailer and brake supply         DOT approved 7 way connector           Lighting System         DOT approved zinc-plate w/two clevis grab hooks           Safety Chains           DOT approved zinc-plate w/two clevis grab hooks           DOT approved zinc-plate w/two clevis grab hooks           Buction Hose           Suction Hose         30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)           Dot approved zinc-plate w/two clevis grab hooks           Fort Size           Suction Hose         30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)           Port Size           Suction Port Size         2" lever valve with Camlock         3" Lever Valve with Camlock         4" Lever Valve with Camlock         4" Lever Valve with Camlock         Camlock <td>Optional Engine</td> <td></td> <td></td> <td>•</td> <td></td>	Optional Engine			•			
Trailer Specs         Galvanized single 5200# Axle, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck           Hitch         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Galvanized spoke           Tires         \$T225/75R15           Jackstand         7,000 lbs           Trailer and brake supply         DOT approved 7 way connector           Lighting System         DOT approved £ED           Safety Chains         DOT approved zinc-plated w/two clevis grab hooks           Hoses           Suction Hose         30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)           Discharge Hose         10 ft Layflat with Alum. Camlock Fittings (longer lengths available)           Port Sizes           Suction Port Size         2" lever valve with Camlock         3" Lever Valve with Camlock         3" Lever Valve with Camlock           Off-Load Port Size         3" Lever Valve with Camlock         4" Lever Valve with Camlocks         4" Lever Valve with Camlocks           Suction Vac Wand:         5 ft PVC Pipe with 90° Camlock         4" Lever Valve with Camlocks         Camlocks           Overall (Approximate)         4" Lever Valve Valv	Power Transmission	Belt Driven					
Hitch         Select: 2" Ball, 2 5/16" ball, 3" Pintle           Wheels         Galvanized spoke           Tires         ST225/75R15           Jackstand         7,000 lbs           Trailer and brake supply         DOT approved 7 way connector           Lighting System         DOT approved LED           Safety Chains         DOT approved zinc-plated w/two clevis grab hooks           Hoses           Suction Hose         30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)           Port Sizes         Port Sizes           Suction Port Size         2" lever valve with Camlock         3" Lever Valve with Camlock         3" Lever Valve with Camlock         4" Lever Valve with Camlock         4" Lever Valve with Camlock         4" Lever Valve with Camlocks         4" Lever Valve w	Trailer						
Wheels         Galvanized spoke           Tires         ST225/75R15           Jackstand         7,000 lbs           Trailer and brake supply         DOT approved 7 way connector           Lighting System         DOT approved LED           Safety Chains         DOT approved zinc-plated w/two clevis grab hooks           Suction Hose         30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)           Port Sizes         30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)           Port Sizes         2" lever valve with Camlock Fittings (longer lengths available)           Port Sizes         2" lever valve with Camlock         3" Lever Valve with Camlock         3" Lever Valve with Camlock         3" Lever Valve with Camlock         2" Lever Valve with Camlock         2" Lever Valve with Camlocks         3" Lever Valve with Camlocks         3" Lever Valve with Camlocks         5 ft PVC Pipe with 90° Camlock         Comlocks         Comlocks         Comlocks         Comlocks         Comlocks         Comlocks         Comlocks         Comlocks         Comlocks         Comlocks <td>Trailer Specs</td> <td colspan="6">Galvanized single 5200# Axle, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck</td>	Trailer Specs	Galvanized single 5200# Axle, E-Brakes, Jack Stand, LED Lighting, Alum. Checker Plate Deck					
Tires ST225/75R15  Jackstand 7,000 lbs  Trailer and brake supply DOT approved 7 way connector Lighting System DOT approved LED  Safety Chains DOT approved LED  Safety Chains DOT approved LED  Suction Hose 30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)  Discharge Hose 10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  Port Sizes  Suction Port Size 2" lever valve with Camlock Camlock Camlock Camlock  Off-Load Port Size 3" Lever Valve with Camlock Camlock Camlock  Suction Vac Wand: 5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (lb): 2000-2700 lbs  GOWR 5200 lbs  Trailer Dimensions 13" Lever Var Var Var Var Var Var Var Var Var Va	Hitch	Select: 2" Ball, 2 5/16" ball, 3" Pintle					
Trailer and brake supply  Trailer and brake supply  DOT approved 7 way connector  DOT approved LED  Safety Chains  DOT approved LED  Safety Chains  DOT approved zinc-plated w/two clevis grab hooks  Hoses  Suction Hose  30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)  Discharge Hose  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  Port Sizes  Suction Port Size  2" lever valve with Camlock  Suction Vac Wand:  5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (lb):  2000-2700 lbs  GVWR  5200 lbs  Trailer Dimensions	Wheels	Galvanized spoke					
Trailer and brake supply Lighting System Safety Chains DOT approved LED  Safety Chains  DOT approved LED  Strailer Dinensions  DOT approved LED  Strailer Dinensions	Tires	ST225/75R15					
Lighting System  Safety Chains  DOT approved zinc-plated w/two clevis grab hooks  Hoses  Suction Hose  30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)  Discharge Hose  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  Port Sizes  Suction Port Size  Suction Port Size  2" lever valve with Camlock Camlo	Jackstand	7,000 lbs					
Safety Chains  DOT approved zinc-plated w/two clevis grab hooks  Hoses  Suction Hose 30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)  Discharge Hose 10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  Port Sizes  Suction Port Size 2" lever valve with Camlock Camlock Camlock Camlock  Off-Load Port Size 3" Lever Valve with Camlock Camlock Camlock  Suction Vac Wand: 5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (lb): 2000-2700 lbs  Loaded 4600-5200 lbs  Trailer Dimensions  DOT approved zinc-plated w/two clevis grab hooks  Fittings (longer lengths available)  3" Lever Valve with Alum. Camlock Fittings (longer lengths available)  3" Lever Valve with 3" Lever Valve with Camlock  Camlock Camlock  Camlock  Camlock  Camlocks  S ft PVC Pipe with 90° Camlock  Discharge Hose 4600-5200 lbs  Trailer Dimensions	Trailer and brake supply		DOT approved	7 way connector			
Suction Hose 30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)  Discharge Hose 10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  Port Sizes  Suction Port Size 2" lever valve with Camlock Camlocks Camlocks  Suction Vac Wand: 5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (Ib): 2000-2700 lbs  Loaded 4600-5200 lbs  GVWR 5200 lbs  Trailer Dimensions 13'L x 6'2" W x 73"H,	Lighting System	DOT approved LED					
Suction Hose  30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)  Port Sizes  Suction Port Size  2" lever valve with Camlock Camlock  3" Lever Valve with Camlock Camlock  3" Lever Valve with Camlock  4" Lever Valve with Camlocks  3" Lever Valve with Camlock  5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (lb):  Loaded  GVWR  Tailer Dimensions  30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  13" Lever Valve with S" Lever Valve with Camlock  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  3" Lever Valve with Camlock  2" Lever Valve with Camlock  4" Lever Valve with Camlock  4" Lever Valve with Camlock  Camlock  5 ft PVC Pipe with 90° Camlock  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock Fittings (longer lengths available)  10 ft Layflat with Alum. Camlock  2" Lever Valve with Camlock  2" Lever Valve with Camlock  2 camlock  2 camlock  2 camlock  5 ft PVC Pipe with 90° Camlock  5 ft PVC Pipe with 90° Camlock  10 ft Layflat with Alum. Camlock  2 camlock  3 camlock  2 camlock  2 camlock  3 camlock  2 camlock  2 camlock  3 camlock  2 camlock  3 camlock  4 camlock  2 camlock  3 caml	Safety Chains	DOT approved zinc-plated w/two clevis grab hooks					
Discharge Hose   10 ft Layflat with Alum. Camlock Fittings (longer lengths available)	Hoses						
Suction Port Size  2" lever valve with Camlock  2" lever Valve with Camlock  Off-Load Port Size  3" Lever Valve with Camlock  4" Lever Valve with Camlock  Camlock  4" Lever Valve with Camlocks  5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (lb):  Loaded  GVWR  Trailer Dimensions  2" lever valve with Camlock  Camlock  4" Lever Valve with Camlocks  Camlocks  Camlocks  4" Lever Valve with Camlocks  Camlocks  Camlocks  4" Lever Valve with Ocamlocks  4" Lever Valve with Ocamlocks  4" Lever Valve with Camlocks  4" Lever Valve with Ocamlocks  4" Lever Valve with Camlocks  4" Lever Valve with Ocamlocks  5 ft PVC Pipe with 90° Camlock  1	Suction Hose	30 ft Non-Collapsible with Alum. Camlock Fittings (longer lengths available)					
Suction Port Size  2" lever valve with Camlock Camlock Camlock  3" Lever Valve with Camlock Camlock  3" Lever Valve with Camlock Camlock  4" Lever Valve with Camlocks  5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (lb):  Loaded  GWR  Trailer Dimensions  2" lever valve with Camlock Camlock  3" Lever Valve with Camlock Camlocks  4" Lever Valve with Camlock  4" Lever Valve with Camlocks  5 ft PVC Pipe with 90° Camlock  5 ft PVC Pipe with 90° Camlock  1	Discharge Hose	10 ft Layflat with Alum. Camlock Fittings (longer lengths available)					
Camlock Camlock Camlock Camlock Camlock  Off-Load Port Size 3" Lever Valve with Camlock 4" Lever Valve with Camlock Camlocks  Suction Vac Wand: 5 ft PVC Pipe with 90° Camlock  Overall (Approximate)  Dry Weight (Ib): 2000-2700 lbs  Loaded 4600-5200 lbs  GVWR 5200 lbs  Trailer Dimensions 13"L x 6'2" W x 73"H,	Port Sizes						
Camlock         Camlocks         Camlocks         Camlocks           Suction Vac Wand:         5 ft PVC Pipe with 90° Camlock           Overall (Approximate)           Dry Weight (lb):         2000-2700 lbs           Loaded         4600-5200 lbs           GVWR         5200 lbs           Trailer Dimensions         13'L x 6'2" W x 73"H,	Suction Port Size						
Overall (Approximate)           Dry Weight (lb):         2000-2700 lbs           Loaded         4600-5200 lbs           GVWR         5200 lbs           Trailer Dimensions         13'L x 6'2" W x 73"H,	Off-Load Port Size						
Dry Weight (lb):       2000-2700 lbs         Loaded       4600-5200 lbs         GVWR       5200 lbs         Trailer Dimensions       13'L x 6'2" W x 73"H,	Suction Vac Wand:	5 ft PVC Pipe with 90° Camlock					
Dry Weight (lb):       2000-2700 lbs         Loaded       4600-5200 lbs         GVWR       5200 lbs         Trailer Dimensions       13'L x 6'2" W x 73"H,	Overall (Approximate)						
Loaded         4600-5200 lbs           GVWR         5200 lbs           Trailer Dimensions         13'L x 6'2" W x 73"H,		2000-2700 lbs					
Trailer Dimensions 13'L x 6'2" W x 73"H,		4600-5200 lbs					
Trailer Dimensions 13'L x 6'2" W x 73"H,	GVWR	5200 lbs					
	Underclearence						





# **BUILD OPTIONS**

#### **CFM Vacuum Power**

CFM or cubic feet per minute relates to vacuum suction power. Wastecorp offers several CFM options. Our industry leading standard CFM is 127. 230 CFM, 350 CFM and 600 CFM are also available. We also offer blower packages for hydro excavation,

127 CFM			
230 CFM			
350 CFM			

## **Engine Options**

Wastecorp offers electric, gas and diesel power options for Super Duty Vacuum Systems.

Gas		
Electric		
Diesel		

#### **Dual Compartment Options**

Select either waste only tanks or waste plus water compartments.



Wastecorp uses premium steel tanks that stand the test of time. We offer dual compartment waste and water or external polyethylene water tanks (your choice)

#### **Jetter Options**

Expand the capabilities of your system with both waste collection and water jetting function. Jetters are ideal for cleaning catch basins, sewer pipes and general facilities maintenance.



Several jetter packages available to meet your job site needs.

#### **SUPER DUTY® VACUUM PUMPS**

Designed and Manufactured by Wastecorp Pumps in USA and/or Canada.

Toll-Free: 1.888.829.2783 Email: info@wastecorp.com International: +1-201-445-2882

#### **Optional Equipment**



**Rear Manway** 

Designed to allow for easy maintenance and cleaning of tank interior.



**Work Light Package** 

Bright LED's for working in dark conditions. Beacon light and traffic diversion arrows (DOT compliant) available.



**Storage Options** 

Locking storage compartments available depending on the model. Various lockable storage options to help deter theft and vandalism.



**Tank Mounted Camera System** 

Wireless reverse assistance making maneuvering your job site easier.

