MUD SUCKER® DIAPHRAGM PUMPS

FAC-M-DD[™] Series

Engine Driven Double Diaphragm Pumps

3FAC-M-DD™

FEATURES

Pump up to 160 GPM

Runs dry without damage

Positive displacement pump

Transfer solids up to 21/4" or 50% by volume

Cast iron pump body

13" diaphragms (x2)

High performance EPDM flapper valves (clack)





PUMP POWER AND DURABILITY UNITE.

THE MUD SUCKER 3FAC-M-DD.

Wastecorp's latest double diaphragm pump, the Mud Sucker® 3FAC-M-DD™ is an advanced technology pump to help you pump the tough stuff. With a redesigned flapper valve system, you can access the suction and discharge internals with the twist of a handle. In seconds you can inspect the area, change the flappers quickly and get back to business.

Select from Honda gas or diesel engine options to get the right pump for your application. With the widest selection of accessories and custom configurations you get the exact pump out you're looking for without long lead times.

Double Diaphragm Pumps With Advanced Flapper Technology



Easy Flapper Access

Access the suction and discharge in seconds. With the twist of a handle you can inspect the suction and discharge or replace flappers.



Heavy Duty Design

Make no mistake, all double diaphragm pumps are not alike. The Mud Sucker features a cast iron pump body with premium components.




TOP Rated Drive Systems

Top rated drive systems available Honda gas or diesel engines.

WHAT THIS MEANS TO YOU.

Heavy duty EPDM flappers help you pump the tough stuff like no other diaphragm pump. Get long life cycles and improve your pumping productivity. Spare parts are affordable and are easy to change. Enhanced performance with engines designed for your pump helps you take advantage of all the Mud Sucker pump can do for you



Mud Sucker electric double diaphragm pumps are manufactured in North America. Country/region specific models are available workdwide.

Performance Range

Max. capacity*	160 GPM	
Max. Suction lift	25'vertical or 75' horizontal	
Max. discharge head	50' vertical or 300' horizontal	
Solids handling	2.250" dia or 50% by volume	

Pump Specifications

Suction inlet/outlet size	3"x3"		
Max. liquid temperature	140°F (60°C) continuous		
Pump body casing	Cast iron		
Diaphragm	13" dia TPE Santoprene® Severe duty		
Flapper valves	EPDM		
Gearbox/Motor	SEW Eurodrive		
Ultimate radial static load capacity	9,000 Lbs		

Motor Specifications

Description	Part No.	
9 hp Honda gas engine w/gear reducer (e-start)	64995-20	
9.1 hp Kohler diesel engine (e-start)	64995-30	

Select from Honda gas engines or Yanmar, Kohler or Hatz diesel


13" Santoprene® diaphragm

Exclusive Wastecorp engineered velocity channel to move fluids without clogging


Pump Internals available with industry specific components

Access flappers in seconds with the exclusive Mud Sucker flapper valve system.

Dimensional Drawing**



Performance Curve



Double Diaphragm Pumps With Advanced Flapper Technology



ACCESSORIES

	Part no.	Description		Part no.	Description
	19022-00	Recommended! Pressure relief valve, bronze set at 40 psi	000	61292-00	ATV wheel kit. Tow with most makes of ATVs.
	65214-00	Basic spare parts kit (diaphragm and flappers)		60466-00	Camlock fitting 3" alum. male adapter MNPT
	65066-00	Comprehensive spare parts kit (diaphragm, flappers gaskets, weights and hardware)	<u>igi</u>	64970-00	Air chamber assembly for pulsation dampening
	60723-00	Non-collapsible EPDM hose 3"x20'. Camlocks included		Various	Wet section coatings for specific applications
(A)	51334-10	Discharge hose, lay flat (brown) 3"x50'. Camlocks included		61245-00	Clear swing check valve 3" FPTxFPT

Mud Sucker® Diaphragm Pumps

Toll-Free: 1.888.829.2783 Email: info@wastecorp.com

Website: http://www.wastecorp.com



OEM Manufacturer