MUD SUCKER® DIAPHRAGM PUMPS FAC-DD[™]

Series

Electric **Double Diaphragm** Pumps

4FAC-EC-DD™

FEATURES

Pump up to 300 GPM

Runs dry without damage

Positive displacement pump

Transfer solids up to 21/2" or 50% by volume

Cast iron pump body

13" diaphragms (x2)

High performance EPDM flapper valves (clack)





ELECTRIC DOUBLE DIAPHRAGM PUMPS WITH NEW FLAPPERS FOR EASY ACCESS.

Wastecorp's latest electric double diaphragm pump, the Mud Sucker® 4FAC-EC-DD™ is an advanced technology pump to help you pump the tough stuff. With a redesigned flapper valve system, you can access the suction and discharge internals with the twist of a handle. In seconds you can inspect the area, change the flappers quickly and get back to business.

Select from single, three phase and explosion proof drive options to get the right pump for your application. With the widest selection of accessories and custom configurations you get the exact pump out you're looking for without long lead times.



Easy Flapper Access

Access the suction and discharge in seconds. With the twist of a handle you can inspect the suction and discharge or replace flappers.



Heavy Duty Design

Make no mistake, all double diaphragm pumps are not alike. The Mud Sucker features a cast iron pump body with premium components.



TOP Rated Drive Systems

Top rated drive systems available in single phase, three phase and explosion proof models.

WHAT THIS MEANS TO YOU.

Heavy duty EPDM flappers help you pump the tough stuff like no other diaphragm pump. Get long life cycles and improve your pumping productivity. Spare parts are affordable and are easy to change.

Enhanced performance with motors designed for your pump helps you take advantage of all the Mud Sucker pump can do for you

MUD SUCKER® DIAPHRAGM PUMPS THE PUMP WITH ATTITUDE.

wastecorp.com

Electric Double Diaphragm Pumps With Advanced Flapper Technology



Mud Sucker electric double diaphragm pumps are manufactured in North America. Country/region specific models are available worldwide.

Performance Range

Max. capacity*	300 GPM	
Max. Suction lift	25'vertical or 75' horizontal	
Max. discharge head	50' vertical or 300' horizontal	
Solids handling	2.5" dia or 50% by volume	

Pump Specifications

Suction inlet/outlet size	4"x4" 140°F (60°C) continuous	
Max. liquid temperature		
Pump body casing	Cast iron	
Diaphragm	14¾" dia TPE Santoprene® Severe duty	
Flapper valves	EPDM	
Gearbox/Motor	SEW Eurodrive/Siemens	
Ultimate radial static load capacity	9.000 Lbs	

Motor Specifications

Description	Part No.	Motor Option
Standard motor, Three phase (TEFC)	64995-00	7.5 HP/1800RPM/3/60/230-460V
Single Phase (TEFC)	64995-10	7.5 HP/1800RPM/1/60/115-230V
Explosion Proof (Three phase, TEXP)	64995-60	7.5 HP/1800RPM/3/60/230-460V (or 575V)
Explosion Proof (Single phase), TEXP	64995-70	5 HP/1800RPM/1/60/115-230V TEXP

Mud Sucker® Diaphragm Pumps

Toll-Free: 1.888.829.2783 Email: info@wastecorp.com Website: http://www.wastecorp.com

Premium Siemens[®], SEW Eurodrive[®] or equivalent drive system

14¾" Santoprene® diaphragm

Exclusive Wastecorp engineered velocity channel to move fluids without clogging

Pump Internals available with industry specific components

Access flappers in seconds with the exclusive Mud Sucker flapper valve system.

Dimensional Drawing



Performance Curve



WASTECORP. Pumps[®] OEM Manufacturer