



Super Duty®

**TVP-200™ Series
Vacuum Pumps**

FEATURES

Designed for septic, waste trap grease, marine, liquid food, chemical containment, sump cleaning

Pumps suspended solids

Dry start suction lift to 25 ft.

Safe to run dry

Low emulsion

Low sheering action

Pumps available to 60 GPM

Automatic continuous duty

Wastecorp is An ISO 9001
and ISO 14001 pump
manufacturer



Pump Specifications

TVP 200

Part No.	65084-00
Pump & motor	1.5 HP @ 20 CFM
Tank	115 gallons
Connections	1½ x 2" NPT Intake & Discharge w/ motorized ball valve
Finish	Powder coat white or hot dipped galv. tank
Hoses	30 ft Intake Hose Assembly
Accessories	Two sizes deck adapters, universal deck adapter, potty wand

Performance Specifications

Max. suction lift	25 ft
Max. suction distance	1200 ft
Max. suction performance	60 GPM
Max. discharge head	30 ft
Max. discharge distance	1500 ft

Approximate Dimensions

Width	34"
Length	60"
Height	55"
Tank diameter	30"
Intake connection	2"
Discharge connection	2"
Empty weight	480 lbs

Super Duty® Professional Vacuum Pumps

• info@wastecorp.com • 1-888-829-2783

WASTECORP.COM