



Super Duty®
TVP-300™ Series
Vacuum Pumps

FEATURES

Designed for septic, waste trap grease, marine, liquid food, chemical containment, sump cleaning

Pumps suspended solids

Dry start suction lift to 25 ft.

Safe to run dry

Low emulsion

Low sheering action

Pumps available to 90 GPM

Automatic continuous duty

Wastecorp is An ISO 9001 and ISO 14001 pump manufacturer

Designed and manufactured in the USA and/or Canada



Pump Specifications		TVP 300
Part No.	65085-00	
Pump & motor	2 HP @ 35 CFM	
Tank	250 gallons	
Connections	1½ x 2" NPT Intake & Discharge w/ motorized ball valve	
Finish	Powder coat white or hot dipped galv. tank	
Hoses	30 ft Intake Hose Assembly	
Accessories	Two sizes deck adapters, universal deck adapter, potty wand	
Performance Specifications		
Max. suction lift	25 ft	
Max. suction distance	1500 ft	
Max. suction performance	90 GPM	
Max. discharge head	30 ft	
Max. discharge distance	2000 ft	
Approximate Dimensions		
Width	36"	
Length	72"	
Height	65"	
Tank diameter	36"	
Intake connection	1½"	
Discharge connection	1½"	
Empty weight	900 lbs	